# NSN 5930-01-065-0762

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-065-0762

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.550 inches

# **Overall Height:**

1.000 inches

#### **Overall Width:**

0.890 inches

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.375 inches single actuator

#### **Nonturn Device Radius:**

# 0.375 inches at 3: 00 o'clock

# Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

1 single section rear

#### **Throw Quantity:**

7 single section rear

# **Mounting Method:**

Threaded bushing single mounting facility

# **Thread Size:**

0.375 inches single mounting facility

# Contact Voltage Rating In Volts:

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

7 single actuator

# Shaft Type:

Round single actuator

# **Terminal Type:**

Clip

# **Contact Switching Action:**

Makes before breaks single section rear

# Switch Actuator Positioning Increment:

45.0 degrees single actuator

# NSN 5930-01-065-0762

Rotary Switch - Page 2 of 2



**Detent Rotational Torque Range:** +15.000/+30.000 inch-ounces single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Terminals silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0