NSN 5930-01-065-0771

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-065-0771

| Hazardous Locations/environmental Protection: |
|---|
| Moisture resistant |
| Overall Length: |
| 0.678 inches |
| Overall Diameter: |
| 0.370 inches |
| Individual Section Quantity: |
| 1 |
| Operating Tempurature Range: |
| -54.0/+125.0 degrees celsius |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 single section rear |
| Throw Quantity: |
| 3 single section rear |
| Mounting Method: |
| Printed circuit single mounting facility |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 3 single actuator |
| Terminal Type: |
| Printed circuit |
| Contact Switching Action: |
| Breaks before makes single section rear |
| Switch Actuator Positioning Increment: |
| 36.0 degrees single actuator |
| Detent Rotational Torque Range: |
| +2.000/+6.000 inch-ounces single actuator |
| Contact Load Current Rating: |
| 300.0 milliamperes resistive load dc at sea level |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Miniature, pin mount |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-01-065-0771

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0