

View Online at <https://aerobasegroup.com/nsn/5930-01-065-2684>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

1.270 inches

Overall Height:

1.160 inches

Overall Width:

0.635 inches

Bushing Length:

0.470 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Body Height:

0.910 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.180 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

Special Features:

Item must comply with requirements of desc production standard no. L02558; for navy nuclear propulsion plant products only

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0