NSN 5930-01-065-2985

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-065-2985

Thread Class: 2a single mounting facility Thread Length: 0.469 inches single mounting facility **Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 3.469 inches First Flat Length: 0.875 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.094 inches single actuator **Overall Diameter:** 2.000 inches **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 7 each section rear **Mounting Method:** Threaded bushing w/panel seal single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.469 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:**

8 single actuator

NSN 5930-01-065-2985Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted, threaded hole single actuator
Criticality Code Justification:
Feat
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Special Features:
Item must comply with requirements of desc production standard no. L02554; for navy nuclear propulsion plant products only
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Reference Number Differentiating Characteristics:
Material will be in accordance with navicp mech; activity hx quality control, manufacturing and testing specifications.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A052b0