NSN 5930-01-065-2987

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-065-2987

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.380 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Plastic
Actuator Length:
0.640 inches
Actuator Style:
Rectangular
Actuator Height:
0.430 inches
Actuator Width:
0.640 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Natural single actuator
Actuator Inscription:
30 khz bw single actuator
Maximum Voltage Rating In Volts:
230.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-065-2987

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Special Features:

Unit has conductive finish

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0