

View Online at <https://aerobasegroup.com/nsn/5930-01-065-2989>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.380 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Plastic

Actuator Length:

0.640 inches

Actuator Style:

Rectangular

Actuator Height:

0.430 inches

Actuator Width:

0.640 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Natural single actuator

Actuator Inscription:

Am single actuator

Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.950 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Special Features:

Unit has conductive finish

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0