NSN 5930-01-065-3009

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-065-3009

| Body Style: |
|---|
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Explosion proof and humidity resistant |
| Overall Length: |
| 3.380 inches |
| Overall Height: |
| 0.750 inches |
| Overall Width: |
| 0.750 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Case Material: |
| Plastic |
| Actuator Length: |
| 0.640 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.430 inches |
| Actuator Width: |
| 0.640 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Natural single actuator |
| Actuator Inscription: |
| Agc single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 2.950 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Full display lens |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, one position momentary single switch unit |

NSN 5930-01-065-3009

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Unit has conductive finish

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0