## NSN 5930-01-065-9298



Pressure Switch - Page 1 of 2	-
View Online at https://aerobasegroup.com/nsn/5930-01-065-9298	
Thread Class:	
3b single pressure connection	
Inside Diameter:	
0.240 inches single connection	
Thread Length:	
0.500 inches single pressure connection	
Overall Length:	
3.500 inches	
Overall Height:	
4.500 inches	
Overall Width:	
2.875 inches	
Body Height:	
2.250 inches	
Distance Between Mounting Facility Centers:	
1.750 inches	
End Application:	
Air route surveillance radar 3 (arsr3)	
Pressure Switch Type:	
Differential	
Mounting Method:	
Bracket	
Thready Qty Per Inch (tpi):	
18 single pressure connection	
Contact Action Stimulus:	
Increase	
Thread Size:	

0.250 inches single pressure connection

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Screw

**Contact Load Current Rating:** 

15.0 amperes resistive load single voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point adjustable

**Contact Adjustment Range:** 

+0.00/+200.00 actuation point pounds per square inch

**Contact Adjustment Type:** 

External actuation point knob with scale

## NSN 5930-01-065-9298

Pressure Switch - Page 2 of 2



Contact	<b>Stimulus</b>	Dating:
Jontact	Stimulus	Ratinu.

0.40 differential point pounds per square inch and 1.10 differential point pounds per square inch

**Contact Voltage Rating In Volts:** 

250.0 ac at sea level single voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

**Special Features:** 

Dust cover included

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

**Thread Series Designator:** 

Nptf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A048b0