

View Online at <https://aerobasegroup.com/nsn/5930-01-065-9298>

Thread Class:

3b single pressure connection

Inside Diameter:

0.240 inches single connection

Thread Length:

0.500 inches single pressure connection

Overall Length:

3.500 inches

Overall Height:

4.500 inches

Overall Width:

2.875 inches

Body Height:

2.250 inches

Distance Between Mounting Facility Centers:

1.750 inches

End Application:

Air route surveillance radar 3 (arsr3)

Pressure Switch Type:

Differential

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+200.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point knob with scale

Contact Stimulus Rating:

0.40 differential point pounds per square inch and 1.10 differential point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

Dust cover included

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0