# NSN 5930-01-066-0891

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-066-0891



#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.380 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### **Case Material:**

Plastic

## Actuator Length:

-----j....

0.640 inches

## Actuator Style:

Rectangular

#### Actuator Height:

0.430 inches

#### Actuator Width:

0.640 inches

#### Actuator Color:

Black single actuator

#### **Illuminated Actuator Color:**

Natural single actuator

#### **Actuator Inscription:**

Medium single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

### Mounting Surface To Terminal End Distance:

2.950 inches

#### Inclosure Type:

Fully enclosed

## Mounting Method:

Panel

### **Features Provided:**

Full display lens

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-066-0891

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

## **Special Features:**

Unit has conductive finish

Precious Material And Location:

Contacts gold

## Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0