NSN 5930-01-066-0896

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-066-0896

| Thread Class: |
|--|
| 2a |
| Body Style: |
| Bushing mounted |
| Overall Length: |
| 1.047 inches |
| Overall Height: |
| 0.375 inches |
| Overall Width: |
| 0.375 inches |
| Body Diameter: |
| 0.375 inches |
| Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.407 inches |
| Case Material: |
| Plastic |
| Actuator Diameter: |
| 0.160 inches |
| Actuator Height: |
| 0.150 inches |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 1.000 amperes resistive dc and 500.000 milliamperes resistive ac |
| Precious Material And Location: |
| Contacts silver |
| Thread Series Designator: |
| Uns |

NSN 5930-01-066-0896

Push Switch - Page 2 of 2



| i ei ii ii iai Tybe And Quantity. | Tε | rminal | Type | And | Quantity: | |
|-----------------------------------|----|--------|------|-----|-----------|--|
|-----------------------------------|----|--------|------|-----|-----------|--|

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0