

View Online at <https://aerobasegroup.com/nsn/5930-01-066-6327>

**Thread Class:**

2a 1st mounting facility

**Thread Length:**

0.312 inches 1st mounting facility

**Overall Length:**

2.047 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.563 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.047 inches 2nd mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.375 inches 2nd mounting facility

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

14 single section rear

**Mounting Method:**

Threaded bushing 1st mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

14 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

22.5 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0