## NSN 5930-01-066-6328

Toggle Switch - Page 1 of 2

Threaded bushing **Features Provided:** 

Actuator seal



View Online at https://aerobasegroup.com/nsn/5930-01-066-6328 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Weatherproof **Overall Length:** 1.320 inches **Overall Height:** 2.620 inches **Overall Width:** 0.890 inches **Bushing Length:** 0.470 inches **Body Length:** 1.320 inches **Body Width:** 0.890 inches **Body Height:** 1.470 inches **Case Material:** Plastic **Actuator Style:** Round **Actuator Diameter:** 0.240 inches **Actuator Height:** 0.680 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Actuator Color:** Natural single actuator **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **End Application:** Helicopter 97499 Inclosure Type: Fully enclosed **Mounting Method:** 

## **NSN 5930-01-066-6328** Toggle Switch - Page 2 of 2



Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, three positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc and 6.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0