

View Online at <https://aerobasegroup.com/nsn/5930-01-066-7144>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.479 inches single pressure connection

**Overall Length:**

1.125 inches

**Outside Diameter:**

0.375 inches single connection

**Body Length:**

1.125 inches

**Overall Diameter:**

1.230 inches

**End Application:**

Aircraft, tomcat f-14

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -55.0 degrees fahrenheit and 204.0 degrees fahrenheit

**Mounting Method:**

Clamp and input port

**Features Provided:**

Electrical access port and hermetically sealed case

**Thready Qty Per Inch (tpi):**

24 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

60.00 pounds per square inch absolute

**Thread Size:**

0.375 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Turret

**Contact Load Current Rating:**

3.0 amperes resistive load single voltage and 1.0 amperes inductive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+26.00/+29.00 actuation point pounds per square inch absolute and +22.00/+26.00 deactuation point pounds per square inch absolute

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Stimulus Rating:**

3.50 differential point pounds per square inch absolute

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0