

View Online at <https://aerobasegroup.com/nsn/5930-01-066-7144>

Thread Class:

3a single pressure connection

Thread Length:

0.479 inches single pressure connection

Overall Length:

1.125 inches

Outside Diameter:

0.375 inches single connection

Body Length:

1.125 inches

Overall Diameter:

1.230 inches

End Application:

Aircraft, tomcat f-14

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -55.0 degrees fahrenheit and 204.0 degrees fahrenheit

Mounting Method:

Clamp and input port

Features Provided:

Electrical access port and hermetically sealed case

Thready Qty Per Inch (tpi):

24 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch absolute

Thread Size:

0.375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Turret

Contact Load Current Rating:

3.0 amperes resistive load single voltage and 1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+26.00/+29.00 actuation point pounds per square inch absolute and +22.00/+26.00 deactuation point pounds per square inch absolute

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

3.50 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0