NSN 5930-01-067-0964

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-067-0964

Thread Class:

2a single mounting facility

Thread Length:

0.156 inches single mounting facility

Overall Length:

1.101 inches

Overall Height:

1.531 inches

Individual Section Quantity:

,

Longest Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded stud single mounting facility

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts and rotor surfaces gold and contacts and rotor silver

NSN 5930-01-067-0964Rotary Switch - Page 2 of 2



Precious Material:
Gold and silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0