

View Online at <https://aerobasegroup.com/nsn/5930-01-067-0968>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.500 inches

Overall Height:

1.260 inches

Overall Width:

0.270 inches

Bushing Length:

0.280 inches

Body Length:

0.500 inches

Body Width:

0.270 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.480 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

20.0 ac and 20.0 dc

End Application:

Cv-3333/u 97871

Mounting Surface To Terminal End Distance:

0.500 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

Special Features:

Terminals at right angle

Precious Material And Location:

Terminal and contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0