NSN 5930-01-067-0973

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-067-0973

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture proof and shock proof
Overall Length:
0.755 inches
Overall Height:
3.060 inches
Overall Width:
0.755 inches
Body Length:
0.755 inches
Body Width:
0.755 inches
Body Height:
2.250 inches
Case Material:
Metal
Actuator Length:
0.755 inches
Actuator Style:
Rectangular
Actuator Width:
0.755 inches
Actuator Color:
Red single actuator and amber single actuator
Illuminated Actuator Color:
Red single actuator and amber single actuator
Actuator Inscription:
High temp alarm/alarm ack single actuator
Illuminated Actuator Color Sequence:
Upper half of actvator red lower half of actuator amber
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit

NSN 5930-01-067-0973

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

'
inductive ac and 1.500 amperes lamp ac
Special Features:
Horizontal split lens
Precious Material And Location:
Contact surfaces gold and contacts silver
Unable To Decode:
Unable to decode and unable to decode
Terminal Type And Quantity:
19 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A053a0