

View Online at <https://aerobasegroup.com/nsn/5930-01-067-2992>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.500 inches

**Overall Height:**

1.252 inches

**Overall Width:**

0.450 inches

**Bushing Length:**

0.296 inches

**Body Length:**

0.450 inches

**Body Width:**

0.500 inches

**Body Height:**

0.410 inches

**Case Material:**

Metal

**Actuator Style:**

Rectangular

**Actuator Height:**

0.450 inches

**Actuator Width:**

0.100 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

Cimmaron class ao, sturgeon class ssn (637), oliver perry class ffg, tarawa class lha, safeguard class ars, los angeles class ssn (688), emory s. Land class as, forrestal class cv, spruance class dd (963).

**Mounting Surface To Terminal End Distance:**

0.506 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contacts and terminals silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0