

View Online at <https://aerobasegroup.com/nsn/5930-01-067-4913>

**Thread Class:**

3b single pressure connection

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

8.000 inches

**Overall Height:**

2.900 inches

**Overall Width:**

4.750 inches

**Unthreaded Mounting Hole Diameter:**

0.265 inches

**Distance Between Mounting Facility Centers:**

4.250 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

7500.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+500.00/+3000.00 actuation point pounds per square inch gage and +500.00/+3000.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Stimulus Rating:**

225.00 actuation point pounds per square inch gage and 125.00 deactuation point pounds per square inch gage and 100.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

480.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0