# NSN 5930-01-067-4913

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-067-4913

Thread Class:
3b single pressure connection
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
8.000 inches
Overall Height:
2.900 inches
Overall Width:
4.750 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Distance Between Mounting Facility Centers:
4.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Flange and unthreaded hole
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
7500.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+500.00/+3000.00 actuation point pounds per square inch gage and +500.00/+3000.00 deactuation point pounds per square inch gage
Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

## NSN 5930-01-067-4913

Pressure Switch - Page 2 of 2



#### **Contact Stimulus Rating:**

225.00 actuation point pounds per square inch gage and 125.00 deactuation point pounds per square inch gage and 100.00 differential point pounds per square inch gage

## **Contact Voltage Rating In Volts:**

480.0 ac at sea level single voltage

## **Pressure Connector Type:**

Plain, threaded internal single connection

#### **Thread Series Designator:**

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0