NSN 5930-01-067-4927



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-067-4927 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 1.661 inches **Overall Height:** 0.437 inches **Overall Width:** 0.460 inches **Body Diameter:** 0.375 inches **Bushing Length:** Between 0.245 inches and 0.255 inches **Body Length:** 0.750 inches **Case Material:** Plastic **Actuator Diameter:** 0.375 inches **Actuator Height:** 0.454 inches **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **End Application:** 485l tacs **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 32

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

NSN 5930-01-067-4927

Push Switch - Page 2 of 2

A053a0



Criticality Code Justification:
Feat
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 250.000 milliamperes resistive ac
Special Features:
Weapon system essential
Precious Material And Location:
Contact and terminal surfaces silver
Thread Series Designator:
Unef
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: