NSN 5930-01-067-7263

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-067-7263

Overall Length:
2.812 inches
Overall Height:
5.000 inches
Body Height:
2.688 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Distance Between Mounting Facility Centers:
1.750 inches
End Application:
4920-00-502-2246
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
200.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.10/+50.50 actuation point pounds per square inch and +0.00/+50.00 deactuation point pounds per square inch
Contact Adjustment Type:

Contact Adjustificht Type

Internal actuation point dial and internal deactuation point dial

NSN 5930-01-067-7263

Pressure Switch - Page 2 of 2



Contact Voltage	Rating Ir	า Volts:
-----------------	-----------	----------

250.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0