

View Online at <https://aerobasegroup.com/nsn/5930-01-067-7264>

**Overall Length:**

3.500 inches

**Outside Diameter:**

0.250 inches single connection

**Overall Height:**

6.744 inches

**Overall Width:**

2.562 inches

**Body Height:**

4.625 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.625 inches

**Longest Vertical Distance Between Mounting Centers:**

1.375 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1300.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

1600.00 pounds per square inch

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+200.00/+900.00 actuation point pounds per square inch and +184.00/+750.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point hex nut and external actuation point hex nut

**Contact Voltage Rating In Volts:**

600.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0