

View Online at <https://aerobasegroup.com/nsn/5930-01-067-7272>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Driptight

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.328 inches

Actuator Height:

1.062 inches

Actuator Free Position Height:

1.812 inches

Housing Height:

1.781 inches

Housing Length:

2.438 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.625 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Value sol 1.0 09647

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

32.0 ounces

Switch Actuating Force:

Between 28.0 ounces and 54.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.219 overtravel inches and 0.156 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes motor dc and 15.000 amperes resistive ac

Special Features:

Tapped hole 0.500-14npsm

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0