

View Online at <https://aerobasegroup.com/nsn/5930-01-067-7272>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Driptight

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.328 inches

**Actuator Height:**

1.062 inches

**Actuator Free Position Height:**

1.812 inches

**Housing Height:**

1.781 inches

**Housing Length:**

2.438 inches

**Housing Width:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.625 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

Value sol 1.0 09647

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

32.0 ounces

**Switch Actuating Force:**

Between 28.0 ounces and 54.0 ounces

**Actuator Movement:**

Between 0.094 pretravel inches and 0.219 overtravel inches and 0.156 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes motor dc and 15.000 amperes resistive ac

**Special Features:**

Tapped hole 0.500-14npsm

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0