

View Online at <https://aerobasegroup.com/nsn/5930-01-067-7315>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof and humidity resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:**

1.700 inches

**Overall Height:**

1.696 inches

**Overall Width:**

1.366 inches

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.178 inches single mounting facility

**Operating Temperature Range:**

-65.0/+100.0 degrees celsius

**Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Thready Qty Per Inch (tpi):**

56 single mounting facility

**Thread Size:**

0.086 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Eight position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7 each section

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 8 positions each section

**Color:**

White each indicator marking

**Precious Material And Location:**

Stator surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular inline indicating

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0