

View Online at <https://aerobasegroup.com/nsn/5930-01-067-7381>

Thread Class:

2a all threaded stud

Thread Length:

0.500 inches single threaded hole and 0.560 inches single threaded hole

Overall Length:

Between 2.470 inches and 2.710 inches

Overall Diameter:

2.160 inches

End Application:

3810-01-025-4782

Pressure Switch Type:

Gage

Mounting Method:

Threaded stud

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches all threaded stud

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

6.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

105.00 actuation point pounds per square inch and 95.00 deactuation point pounds per square inch and 10.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

14.5 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded external single connection

Thread Series Designator:

Unf all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0