

View Online at <https://aerobasegroup.com/nsn/5930-01-067-7928>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.938 inches

Overall Height:

3.875 inches

Overall Width:

4.250 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

3.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+100.00 actuation point pounds per square inch and +0.00/+100.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0