

View Online at <https://aerobasegroup.com/nsn/5930-01-067-7928>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.938 inches

**Overall Height:**

3.875 inches

**Overall Width:**

4.250 inches

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.625 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

150.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.00/+100.00 actuation point pounds per square inch and +0.00/+100.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point hex nut and internal actuation point hex nut

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A048b0