NSN 5930-01-067-9794

5.00 differential point pounds per square inch

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-067-9794

Overall Length:
4.562 inches
Overall Height:
4.343 inches
Overall Width:
3.500 inches
Body Width:
3.437 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Distance Between Mounting Facility Centers:
2.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port and tamper proof cap
Thready Qty Per Inch (tpi):
14 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
300.00 pounds per square inch
Thread Size:
0.500 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, double break/double make, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
10.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+7.50/+150.00 actuation point pounds per square inch and +1.50/+144.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:

NSN 5930-01-067-9794

Pressure Switch - Page 2 of 2



Contact '	Voltage	Rating	ln	Volts:
Contact	voitage	Rating	ın	voits:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Thread Series Designator:

Nps single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0