

View Online at <https://aerobasegroup.com/nsn/5930-01-067-9873>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.530 inches

Overall Height:

1.360 inches

Overall Width:

0.530 inches

Bushing Length:

0.320 inches

Body Length:

0.530 inches

Body Width:

0.530 inches

Body Height:

0.360 inches

Case Material:

Metal

Actuator Style:

Rectangular

Actuator Height:

0.410 inches

Actuator Width:

0.200 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

End Application:

Nsa-2125/g 98230

Mounting Surface To Terminal End Distance:

0.510 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes inductive dc and 2.000 amperes inductive ac

Precious Material And Location:

Terminals and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0