NSN 5930-01-068-0847

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-068-0847

| view Offilite at https://aerobasegroup.com/hsi//5550-01-000-00-7 |
|---|
| Inside Diameter: |
| 0.125 inches single connection |
| Overall Length: |
| 1.438 inches |
| Overall Height: |
| 3.203 inches |
| Overall Width: |
| 1.438 inches |
| Body Height: |
| 2.688 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.201 inches |
| Distance Between Mounting Facility Centers: |
| 0.625 inches |
| Pressure Switch Type: |
| Gage |
| Mounting Method: |
| Unthreaded hole |
| Contact Action Stimulus: |
| Increase |
| Proof Pressure: |
| 4500.00 pounds per square inch |
| Thread Size: |
| 0.125 inches single pressure connection |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Terminal Type: |
| Wire lead |
| Contact Load Current Rating: |
| 5.0 amperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point adjustable and deactuation point adjustable |
| Contact Adjustment Range: |
| +940.00/+3000.00 actuation point pounds per square inch and +800.00/+2680.00 deactuation point pounds per square inch |
| Contact Adjustment Type: |
| External actuation point knob and external deactuation point knob |
| Contact Voltage Rating In Volts: |

Contact voltage maning in volte.

250.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

NSN 5930-01-068-0847

Pressure Switch - Page 2 of 2



| Frequency In Hertz: |
|--------------------------------|
| 60.0 second voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Rectangular |
| Thread Series Designator: |
| Npt single pressure connection |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A048b0