NSN 5930-01-068-1643

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-068-1643
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
2.657 inches
Overall Height:
2.500 inches
First Flat Length:
0.750 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.219 inches single actuator
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Knob Specificationial Markings:
White arrow symbol
Switch Contact Basic Design:
Nonpile-up symmetrical and nonpile-up nonsymmetrical
Pole Quantity:
1 2nd section rear
Throw Quantity:
2 2nd section rear
Mounting Facility Circle Radius:
2.328 inches single mounting facility
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

NSN 5930-01-068-1643Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, parallel flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes 2nd section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Special Features:
First spacer blank
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0