NSN 5930-01-068-2553

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-068-2553

| Body Style: |
|---|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 5.703 inches |
| Overall Width: |
| 2.312 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 1.500 inches |
| Actuator Style: |
| Roller arm |
| Actuator Roller Diameter: |
| 0.750 inches |
| Actuator Roller Width: |
| 0.250 inches |
| Housing Height: |
| 2.062 inches |
| Housing Length: |
| 4.953 inches |
| Housing Width: |
| 2.312 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 4.219 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width: |
| 1.812 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 600.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 inch-ounces |
| Switch Actuating Force: |
| 150.0 inch-ounces |
| Actuator Movement: |
| 17.0 pretravel degrees and 80.0 overtravel degrees and 11.0 differential degrees |

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 1.200 amperes resistive ac

NSN 5930-01-068-2553 Sensitive Switch - Page 2 of 2

No Fiig: A053a0

