# NSN 5930-01-068-2553

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-068-2553

# **Body Style:**

Hole mounted

### Hazardous Locations/environmental Protection:

Watertight

# **Overall Length:**

5.703 inches

## **Overall Width:**

2.312 inches

#### **Case Material:**

Metal

#### Actuator Length:

1.500 inches

#### **Actuator Style:**

Roller arm

#### Actuator Roller Diameter:

## 0.750 inches

Actuator Roller Width:

0.250 inches

## Housing Height:

2.062 inches

## Housing Length:

4.953 inches

# Housing Width:

2.312 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

#### Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

### Inclosure Type:

Fully enclosed

### Nonpile-up Contact Arrangement:

1 two circuit, one position momentary single switch unit

#### Switch Release Force:

4.0 inch-ounces

## Switch Actuating Force:

150.0 inch-ounces

## **Actuator Movement:**

17.0 pretravel degrees and 80.0 overtravel degrees and 11.0 differential degrees

# Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 1.200 amperes resistive ac

# NSN 5930-01-068-2553

Sensitive Switch - Page 2 of 2



Extra Long Reference Number:

NI100ws1m1 with assembled lever arm aa

# Terminal Type And Quantity:

4 tab w/screw

# **Reference Number Differentiating Characteristics:**

As differentiated by extra long reference number

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A053a0