

View Online at <https://aerobasegroup.com/nsn/5930-01-068-9476>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.880 inches

Overall Height:

0.620 inches

Overall Width:

0.620 inches

Body Diameter:

0.620 inches

Bushing Length:

0.440 inches

Body Length:

1.000 inches

Case Material:

Metal

Actuator Diameter:

0.380 inches

Actuator Height:

0.280 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

F-16 comb fighter

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.500 amperes inductive dc and 500.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 500.000 milliamperes lamp ac

Special Features:

0.880 in. Dia, 0.190 in. H, dress seal ring on bushing

Precious Material And Location:

Terminals and contacts gold

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Specification Data:

81349-mil-s-8805/99 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0