NSN 5930-01-069-0335

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-069-0335

Hazardous I	Locations/	/environmental	Protection:
-------------	------------	----------------	-------------

Explosion proof

Overall Length:

0.760 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.125 inches single actuator

Overall Diameter:

0.562 inches

Individual Section Quantity:

4

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

End Application:

F-5f aircraft 76823

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Flange single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at sea level

NSN 5930-01-069-0335Rotary Switch - Page 2 of 2



Precious Material And Location:		
Terminals gold and wipers silver		
Precious Material:		
Gold and silver		
Style Designator:		
Snap or line		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		

No Fiig: A052b0