NSN 5930-01-069-0341

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Dustproof



View Online at https://aerobasegroup.com/nsn/5930-01-069-0341

Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.816 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.340 inches
Maximum Voltage Rating In Volts:
210.0 ac and 30.0 dc
End Application:
An-alq-t5 97384
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
7.0 grams
Switch Actuating Force:
40.0 grams
Actuator Movement:
Between 0.085 pretravel inches and 0.011 overtravel inches and 0.019 differential inches

NSN 5930-01-069-0341

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0