NSN 5930-01-069-0344

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-069-0344

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.635 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.531 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.531 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Green single actuator and green single actuator

Actuator Inscription:

Eng apu/cart single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.535 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Horizontal split lens

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

NSN 5930-01-069-0344

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes

inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0