NSN 5930-01-069-1817

Pressure Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-069-1817 |
|---|
| Thread Class: |
| 3b single pressure connection |
| Inside Diameter: |
| 0.438 inches single connection |
| Thread Length: |
| 0.500 inches single pressure connection |
| Overall Length: |
| 3.250 inches |
| Body Length: |
| 2.170 inches |
| Overall Diameter: |
| 1.380 inches |
| Pressure Switch Type: |
| Gage |
| Mounting Method: |
| Clamp |
| Features Provided: |
| Electrical access port |
| Thready Qty Per Inch (tpi): |
| 20 single pressure connection |
| Contact Action Stimulus: |
| Increase |
| |

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

2500.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load third voltage and 2.5 amperes inductive load third voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+50.00/+125.00 actuation point pounds per square inch and +35.00/+110.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point pointer and internal deactuation point pointer

Contact Stimulus Rating:

99.00 actuation point pounds per square inch and 84.00 deactuation point pounds per square inch and 15.00 differential point pounds per square inch

NSN 5930-01-069-1817

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Cylindrical Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure: -- Demilitarization:

No Fiig: A048b0