## NSN 5930-01-069-3846



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-069-3846 **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Waterproof **Overall Length:** 2.110 inches **Overall Height:** 0.562 inches **Overall Width:** 0.562 inches **Body Diameter:** 0.562 inches **Bushing Length:** 0.425 inches **Body Length:** 1.050 inches **Case Material:** Metal **Actuator Length:** 0.408 inches **Actuator Style:** Rectangular **Actuator Height:** 0.440 inches **Actuator Width:** 0.408 inches **Actuator Color:** White single actuator **Actuator Inscription:** 1 single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi):

32

**Thread Size:** 

0.469 inches

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary single switch unit

## NSN 5930-01-069-3846

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Special Features:** 

Clear illuminated actuator color

**Precious Material And Location:** 

Contacts gold

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

2 tab, solder lug and 3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0