

View Online at <https://aerobasegroup.com/nsn/5930-01-069-4489>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.313 inches 1st mounting facility

**Overall Length:**

2.458 inches

**Overall Height:**

3.126 inches

**Overall Width:**

3.126 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.687 inches single actuator

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches 2nd mounting facility

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

48 single section rear

**Mounting Method:**

Threaded bushing 1st mounting facility

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

48 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

7.5 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Current carrying parts surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0