## NSN 5930-01-069-5016

Sensitive Switch - Page 1 of 2

Body Style:
Hole mounted
Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-069-5016

1.575 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.984 inches
Overall Height:
2.638 inches
Overall Width:
0.640 inches
Body Length:
1.575 inches
Body Width:
0.630 inches
Body Height:
1.732 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.200 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.122 inches
Actuator Roller Diameter:
0.490 inches
Actuator Roller Width:
0.180 inches
Maximum Voltage Rating In Volts:
240.0 ac and 30.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
43.0 ounces

Between 0.071 pretravel inches and 0.118 overtravel inches and 0.004 differential inches

**Actuator Movement:** 

## NSN 5930-01-069-5016

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 5.000 amperes resistive ac and 200.000 milliamperes inductive ac

**Terminal Type And Quantity:** 

4 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0