## NSN 5930-01-069-7164

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-069-7164 **Overall Length:** 3.320 inches **Overall Height:** 1.875 inches **Overall Width:** 2.640 inches **Mounting Slot Width:** 0.220 inches **Body Length:** 2.320 inches **Distance Between Mounting Facility Centers:** 2.187 inches **Capillary Tube Length:** 48.000 inches **Tempurature Sensing Element Type:** Capillary tube **Mounting Method:** Bracket and slot **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained **Terminal Type:** Screw **Contact Load Current Rating:** 8.0 amperes resistive load second voltage and 40.0 amperes motor load second voltage **Contact Adjustability:** Deactuation point adjustable and actuation point adjustable **Contact Adjustment Range:** +38.05/+41.05 actuation point degrees fahrenheit and +41.60/+46.40 deactuation point degrees fahrenheit **Contact Adjustment Type:** External deactuation point screw and external actuation point screw **Contact Voltage Rating In Volts:** 230.0 ac at altitude second voltage Frequency In Hertz: 60.0 second voltage Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

## NSN 5930-01-069-7164

Thermostatic Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0