

View Online at <https://aerobasegroup.com/nsn/5930-01-069-7164>

**Overall Length:**

3.320 inches

**Overall Height:**

1.875 inches

**Overall Width:**

2.640 inches

**Mounting Slot Width:**

0.220 inches

**Body Length:**

2.320 inches

**Distance Between Mounting Facility Centers:**

2.187 inches

**Capillary Tube Length:**

48.000 inches

**Temperature Sensing Element Type:**

Capillary tube

**Mounting Method:**

Bracket and slot

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

8.0 amperes resistive load second voltage and 40.0 amperes motor load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+38.05/+41.05 actuation point degrees fahrenheit and +41.60/+46.40 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

230.0 ac at altitude second voltage

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0