

View Online at <https://aerobasegroup.com/nsn/5930-01-069-7164>

Overall Length:

3.320 inches

Overall Height:

1.875 inches

Overall Width:

2.640 inches

Mounting Slot Width:

0.220 inches

Body Length:

2.320 inches

Distance Between Mounting Facility Centers:

2.187 inches

Capillary Tube Length:

48.000 inches

Temperature Sensing Element Type:

Capillary tube

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

8.0 amperes resistive load second voltage and 40.0 amperes motor load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+38.05/+41.05 actuation point degrees fahrenheit and +41.60/+46.40 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

230.0 ac at altitude second voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0