NSN 5930-01-069-7176

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-069-7176

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Width:

1.650 inches

Case Material:

Metal

Actuator Style:

Roller arm

Actuator Free Position Height:

1.940 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.320 inches

Actuator Adapter Style:

Roller arm

Housing Height:

1.780 inches

Housing Length:

2.840 inches

Housing Width:

1.650 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.342 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

440.0 ac and 355.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

40.0 ounces

Actuator Movement:

 $0.040 \ pretravel$ inches and $0.280 \ overtravel inches and <math display="inline">0.020 \ differential inches$

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 6.000 amperes resistive ac

NSN 5930-01-069-7176

Sensitive Switch - Page 2 of 2

Special Features:

Counter balanced roller lever

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

