

View Online at <https://aerobasegroup.com/nsn/5930-01-069-9492>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.375 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

10.563 inches

Overall Height:

2.906 inches

Overall Width:

2.812 inches

Unthreaded Mounting Hole Diameter:

0.221 inches 2nd mounting facility

Individual Section Quantity:

10

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

2.000 inches 2nd mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches 2nd mounting facility

End Application:

Panel control 96169

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section periphery

Throw Quantity:

8 each section periphery

Mounting Method:

Threaded bushing 1st mounting facility

Features Provided:

Actuator knob

Thread Size:

0.625 inches 1st mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Isosceles triangle 2nd mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

Two stop screws supplied for switch limiting

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0