

View Online at <https://aerobasegroup.com/nsn/5930-01-069-9506>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus resistant and humidity resistant and vibration resistant

Overall Length:

2.490 inches

Overall Height:

1.015 inches

Overall Width:

1.015 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

1.375 inches

Housing Diameter:

1.015 inches

Housing Length:

1.115 inches

Housing Bushing Length:

1.000 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

240.0 ounces

Switch Actuating Force:

380.0 ounces

Actuator Movement:

Between 0.055 pretravel inches and 0.040 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0